

## Case Study of Mobilize Lubricious Compounds

Compounding Solutions hired an independent 3rd party medical device contract manufacturer specializing in catheter manufacturing and testing to conduct a case study to review the effects of Pebax 6333 SAO1 MED & Pebax 2533 SAO1 MED loaded with Mobilize, a lubricious additive, against natural Pebax resins.

### SCOPE

Both Pebax 6333 and Pebax 2533 were compounded using a 27mm twin screw co-rotating extruder at Compounding Solutions. These resins were extruded into 20" long sections of tubing with outer and inner diameters of 0.081" and 0.069", respectively. The tubing was then tested for the following:

- Dimensional Stability
- Insertion Force
- Flow Rate
- Shaft Leak Test
- Tensile Strength


### SUMMARY

- The natural Pebax and Mobilize compounds were extruded and laminated using the same processing parameters. No changes in processing were necessary.
- No significant effects on tensile strength, shaft leak test, flow rate or dimensional stability were observed amongst the Mobilize compounds.
- The Mobilize compounds reduced the insertion force by 30% compared to natural Pebax.
- Incorporating Mobilize into a typical catheter build can reduce the cost of the device by as much as 50%.

### RESULTS


**Dimensional Stability:** The outer diameter was measured at five points along each 20" section of tubing using a laser micrometer. The average outer diameter of 15 tubes of each material is shown in Figure 1. There is no significant difference between the various materials.

Figure 1. Extruded tubing dimensional stability.



**Insertion Force:** The tubes were inserted through a track which simulated a fistula fixture. This contained a bend radius of 1" and used a standard 7-French introducer. All samples were conditioned in 37°C deionized water. The average force required to insert 15 tubing shafts of each material is shown in Figure 2. A 30% reduction of required insertion force was found using the Mobilize additive in both the hard and soft grades of Pebax.


Figure 2. Required tube insertion force.



## Case Study of Mobilize Lubricious Compounds


**Flow Rate:** This test measures the time required for a given volume of water to pass through the shaft under constant pressure. Two shafts were bonded onto a standard over-the-wire hub, leaving a clearance of 0.001213 in<sup>2</sup>. Through this clearance, 37°C deionized water was drawn at a constant pressure. The average time required for 10mL liquid to flow is shown in Figure 3. There is no significant difference between all materials.

**Figure 3. Time required for 10mL of water to pass through shaft at constant pressure.**




**Shaft Leak Test:** The tubing was tested for leaks using a HBLT leak test machine. The average failure pressure of 15 tubes is shown in Figure 4. No significant difference was observed between the loaded and natural tubing.

**Figure 4. Pressure at which leak was detected on HBLT leak test machine.**



**Tensile Strength:** Tubing samples were tested according to ISO-1055:2013. The samples were strained until failure. The average peak load of 10 tubing samples of each material is shown in Figure 5. There is no significant difference between natural and loaded tubes.

**Figure 5. Peak tensile load applied to tubing.**



## Case Study of Mobilize Lubricious Compounds - Dollarization

Compounding Solutions has presented the benefits of adding the Mobilize additive to increase lubricity. Moreover, adding Mobilize to your catheter tubing compound can save you money. Shown below is a simple catheter build using an etched PTFE liner, Pebax with BaSO<sub>4</sub> outer layer, FEP shrink tubing and a hydrophilic coating versus a catheter build made with Pebax, BaSO<sub>4</sub> & Mobilize outer layer.

Component	Catheter Build without Mobilize	Catheter Build with Mobilize	Notes
PTFE Liner @ 4ft length	\$5 per length	\$0.00	The PTFE liner can be eliminated with the benefits of reduced insertion force and ease of removal from mandrel with Mobilize.
Pebax Compound Outer Layer @ 4ft length	\$2.40 per length	\$2.60 per length	The cost of 50lbs of Pebax with BaSO <sub>4</sub> compound = \$30/lb. The cost of 50lbs of Pebax with BaSO <sub>4</sub> & Mobilize compound = \$60 /lb.
FEP Shrink Tubing @ 4ft length	\$5 per length	\$5 per length	Necessary cost in building of the catheter.
Hydrophillic Coating @ 4ft length	\$4 per length	\$0.00	The Mobilize additive reduces the coefficient of friction by 30% of both the inner and outer surface.
<b>TOTAL</b>	<b>\$16.40 per length</b>	<b>\$7.60 per length</b>	<b>54% COST REDUCTION</b>

The above dollarization does not consider the most recent discovered benefit of Mobilize, increased production speed. Customers have reported a significant reduction in die head pressure, allowing for up to 15% faster line speed/output rate, realizing reduced operating costs.

Compounding Solutions  
258 Goddard Road  
Lewiston, ME 04240

Phone: 207-777-1122  
Fax: 207-777-1566  
info@compoundingolutions.net  
www.compoundingolutions.net

Disclaimer: Compounding Solutions strictly prohibits the use of any Mobilize compounds, including medical grades, in applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. Unless Compounding Solutions otherwise expressly agrees by written contract, the Compounding Solutions trademarks and the Compounding Solutions name shall not be used in conjunction with customers' medical devices, including without limitation, permanent or temporary implantable devices, and customers shall not represent to anyone else, that Compounding Solutions allows, endorses or permits the use of Compounding Solutions products in such medical devices. Further, all implantable medical devices, whether permanent or temporary, carry a risk of adverse consequences. With regard to implantable medical devices, you should not rely upon the judgment of Compounding Solutions. Any decision regarding the appropriateness of a particular medical device in a particular medical application or for a specific clinical use should be based upon the judgment of your physician, medical device supplier and the United States Food & Drug Administration and/or the European process of Medical Device notification. Unless otherwise specifically stated by Compounding Solutions in writing, Compounding Solutions does not perform clinical medical studies on implantable medical devices. Compounding Solutions cannot weigh the benefits against the risks of a device and does not offer a medical judgement on the safety or efficacy of use of any Compounding Solutions product in a medical device. The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, COMPOUNDING SOLUTIONS expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement.

See Safety Data Sheet for Health & Safety Consideration

Find us on:

